

Technical Data

190-600V DIESEL 01-01-2012



Perkins Engine: 1506A-E88TAG2 <i>Electronic Governor</i>	Alternator: Leroy-somer LSA46.2L6	Generator Model:	TPE230 (Open)
	Optional: Stamford UCDI274J Tide TPA274L10		TPE230C (Silent)

50Hz 1500 r.p.m	3 Phase 4 Wires	Power Factor: $\cos \phi = 0.8$	Emissions Certification:	N/A
---------------------------	---------------------------	---	---	-----

RATINGS	Prime Power		Standby Power		Rated Current	
	(PRP)		(LTP)		(A)	
Voltage (V)	kW	kVA	kW	kVA	Amps	
440/254	184	230	200	250	301.8	
415/240	184	230	200	250	320.0	
400/230	184	230	200	250	332.0	
380/220	184	230	200	250	349.5	

RATINGS:

All three Phase generator sets are rated at 0.8 power factor. All single-phase generator sets are rated at 0.8 or 1.0 power factor. **TIDE Power** reserves the right to change the design or specifications without notice and without any obligation or liability whatsoever.

Prime Power:

Available continuously at variable load in lieu of commercially purchased power for an unlimited number of hours per year in accordance with ISO8528-1, and an overload of 10% permitted for one hour in every twelve hours of operation in accordance with ISO 3046-1.

Standby Power:

Emergency Standby Power in variable load applications in accordance with ISO8528-1 in the event of a utility power failure. No overload available for this service as relevant alternators are peak continuous rated at 27°C.

Standard Features

- ▲ High efficient water cooled diesel engine
- ▲ Brushless alternators (Class H, with AVR.)
- ▲ Heavy duty rubber anti-vibration mountings
- ▲ 12/24V starter batteries and connecting cables
- ▲ Separate engine-drive battery charging alternator
- ▲ Industrial silencer for open type generator sets
- ▲ Residential silencer for silent type generator sets
- ▲ Auto start / Digital Tide Easycon Control Panel
- ▲ Wiring with IEC standard
- ▲ Factory Test Certificate
- ▲ Operation & Maintenance Manual & Diagrams
- ▲ Worldwide Product / Technical Support
- ▲ Radiator with cap and drain point.
- ▲ Fully guarded engine driven fan
- ▲ Circuit Breaker - 3 pole (MCCB)
- ▲ Base fuel tank for 6 - 8 hours running at 100% load
- ▲ Oil filter - Diesel filter - Air filter
- ▲ Fully welded steel baseframe with lifting and fork-lifting facilities.
- ▲ Sound proof & Weather protective enclosures for silent type generator sets.


Optional

- △ Automatic Transfer Switch (ATS)
- △ Water - fuel separator
- △ Water heater for severe cold weather
- △ Lub-oil heater for severe cold weather
- △ 50°C-60°C Radiator
- △ Dual wall fuel tank base
- △ Fuel level sensor
- △ Maintenance free battery
- △ Additional **CE Features** Selection
- △ Extra air filters for time-maintenance
- △ Extra diesel filters for time-maintenance
- △ Extra oil filters for time-maintenance
- △ Separated standing fuel tank
- △ Low coolant level sensor
- △ Full range of attachments and options available for alternator

Overall Dimensions (mm) & Weight (kg)


Open Type

Length:
2700
Width:
1000
Height:
1650
Weight:
1650



Silent Type

Length:
3900
Width:
1300
Height:
1950
Weight:
3900



Dimension and design are subject to change without notice.

Warranty

The goods of Tide Power System are under warranty against defects in materials and workmanship for a period of 12 months or 1000 hours whichever come first from the date of delivery to the end user (except the damageable spare parts of genset caused by incorrect man-made operation), and that the aforementioned warranty for the same token is back up by the engine & alternator manufactures and their global distributors.

Engine Specification

50HZ

General Performance

Manufacture	Perkins
Engine Model	1506A-E88TAG2
Engine Type	4 stroke, In-line, 6-cylinder
Engine Speed	1500 r.p.m
Prime Power	205kW/275hp
Standby Power	228kW/306hp
Governor Type	Electronic
Direction of Rotation	Anticlockwise facing flywheel
Air Intake Way	Air to air after cooled, turbocharged
Displacement	8.8 L
Cylinder Bore * Stroke	112mm × 149mm
NO. of Cylinders	6
Compression Ratio	16.1:1
Brake Mean Effective Pressure	1936-2145 kPa
Mean Piston Speed	7.4 m/s
Combustion Air Flow	14.4 m ³ /min
Engine coolant flow	140 L/min

Exhaust System

Exhaust Gas Flow	34.4 m ³ /min
Exhaust Gas Temperature	467 °C
Maximum Back Pressure	10 kPa
Exhaust Outlet, Internal Diameter	NA

Induction System

Maximum Air Intake Restriction	
- Clean Filter	3.7 kPa
- Dirty Filter	6.2 kPa
- Air Filter Type	Dry Paper

Lubrication System

Total lubrication system capacity	41 Litres
Sump capacity only .	36 Litres
Oil temperature (in sump) maximum	120 °C
Oil consumption (highest rating)	<0.1% of fuel

Fuel System

Type Of Injection	Direct Injection
Lift Pump Fuel Delivery	38 Litres/hour
Fuel Consumption at 100% Standby power	51.5 Litres/hour
Fuel Consumption at 100% Prime power	48.6 Litres/hour
Fuel Consumption at 75% Prime power	35.7 Litres/hour
Fuel Consumption at 50% Prime power	23.5 Litres/hour
Fuel Tank Capacity	
- Open Type Genset	8 Hours at Full Load
- Silent Type Gensets	388 Litres

Cooling System

Total System Capacity	29.6 Litres
- Engine	13.9 Litres
- Radiator □	12.6 Litres
Thermostat Operation Range	87-98 °C
Maximum Top Tank Temperature	107°C

Electric System

Electrical System Voltage	24V
Battery	Maintenance-free
Connecting Cables	Available

Energy balance

Energy to coolant	93-99 kW
Energy to Exhaust	144-146 kW
Energy to Radiation	14 kW

Alternator Specification

General Data

Manufacture / Brand	Leroy-somer
Model	LSA46.2L6
AVR Model	R250
Coupling / Bearing	Direct / Single Bearing
Phase	3 Phase
Power Factor	Cos ϕ = 0.8
Winding pitch - Code	2/3 - (N° 6)
Drip Proof	IP 23
Excitation	Shunt

50HZ/1500R.P.M

Prime Output Power	200kW/250kVA
Standby Output Power	220kW/275kVA
Insulation class	H
Voltage regulation	± 0,5 %
Total harmonic TGH/THC at no load	<2,5% - on load <2,5%
Wave form : NEMA = TIF - (*)	< 50
Wave form : I.E.C. = THF	< 2 %
Altitude	≤ 1000 m
Overspeed	2250 min ⁻¹

TIDE Easycon Control Systems

“Let your Generator always in Control”

TIDE Power comprehensive Easycon range control panels are compact, versatile and easy to use.

Easycon 2.0L/H (GU601A / Deepsea DSE3110) panel is a key-start auto control panel, it's a basic control panel fits for generators up to 100kVA to provide basic operating parameters display and protection.



Easycon 3.0 L/H (GU3321 / Deepsea DSE7210) panel is an auto & digital control panel, it's an entry level control panel which provides full power monitoring and protection facilities. All operating parameters are with LCD display. (Auto Main Failure Version DSE7220 also Available.)



Easycon 4.0L/H (GU620A / Deepsea DSE7310) panel is an auto & digital & Remote control panel which includes all the features of Easycon 3.0, and plus data communication of full telemetry via the RS232/RS485 interfaces, CANBus is also included. (Auto Main Failure Version DSE7320 also Available.)



Specifications

4 . 0 L / H	3 . 0 L / H	2	Over Speed pre-alarm & shutdown -	Auto Start -	
		.	Low Oil Pressure Pre-Alarm & shutdown -	Oil Pressure -	
		0	High Water Temp. Pre-alarm & shutdown -	Genset Running Hours -	
		L	Volts, Current, Frequency, Rpm (Instruments)-	Battery Voltage and Charging -	
		/	Fuel Sensor as optional -		
		H	AMF Module as optional -		
				Digital Control Panel -	Switch Opening as Optional -
				Overcurrent Pre-alarm -	AMF Module as optional -
				Overcurrent Shutdown -	Power Factor -
			Prefix Start, Service Indicate, Fault History for Deepsea Module.-		
		Remote Start (Data communication of full telemetry via the RS232/RS485) -			
		CANBus -			

Options

Easycon 5.0H (Deepsea DSE8610) panel fits for Gen-Gen automatic Synchronising and load sharing.

Easycon 6.0H (Deepsea DSE8620) panel fits for Single Gen - Mains automatic Synchronising.

Deepsea DSE7560 Synchronising Controller for Multi gen – Mains Synchronising. This is a separate control unit which enables multiple Easycon 5.0 equipped Gens to be synchronised with the Mains supply.

(For details specifications of Control Panels, please consult our sale department.)

Circuit Breaker

3 Pole MCCB - Standard (4 Pole as optional)

The generators are supplied together with a circuit breaker that permits a thermal protection against overloads and magnetic protection against short-circuit.

Automatic Transfer Switch

A.T.S - 4 Poles

TIDE Power offers not only a changeover switch but also an integrated mains detection and switch system for your 24 Hour Power Protection. The system enables automatic start-up and operation of the generating set in the event of a mains power failure, overvoltage or loss of phase; and also mains automatic re-transfer once it come back.

ATS: Automatically transfer and re-transfer load from main power to gen-power without operator intervention. (Both Automatic and manual operation.)

Please consult our sales department for specifications.



Enclosure / Canopy

(Sound-attenuated & Weather Protective)

“Ensure a quieter life with our sound attenuation system.”

Features:

Extremely Rugged &

Highly Corrosion Resistant Construction

- ▲ Body made from 2.0mm sheet steel components with powder coating
- ▲ 8-12 hours built-in fuel tank integrated into the skid-mount base
- ▲ Excellent design and craftsmanship
- ▲ Zinc alloy with black powder coated or Bright polished stainless steel hinges tested and proven to withstand corrosive conditions.
- ▲ Compact structure and longer service life

Easy Commissioning and Maintenance

- ▲ Separate & Standing control cabinet at one side, quick fix electrical power connections.
- ▲ Lube oil drain and radiator drain
- ▲ Side doors allowing 180° opening rotation
- ▲ Radiator fill access through cover in canopy roof.
- △ Sockets and Lifting shelf as Optional

Security and Safety

- ▲ Earth leakage protection
- ▲ 40-50mm non-flammable sponge inside
- ▲ Control panel viewing window in a lockable access door
- ▲ Emergency stop button mounted on canopy exterior
- ▲ Fuel fill and battery can only be reached via lockable access doors
- ▲ Exhaust silencing system enclosed for operator safety
- ▲ Excellent cooling system to avoid high water temp., reliable operation under harshest conditions.
- ▲ (Ambient temp. upto 40-52°C and altitudes up to 1000M)

Transportability

- ▲ Lifting points on baseframe
- ▲ Lifting shelf as optional

Quiet (Reduce Sound and Vibration)

Noice Level:

77-88dBA at 1m & 67-78dBA at 7m