

# DIESEL GENERATOR SET

## MTU 12V4000 DS1750

1750 kWe / 60 Hz / Standby  
380 - 4160V

Reference MTU 12V4000 DS1750 (1600 kWe) for Prime Rating Technical Data



### SYSTEM RATINGS

#### Standby

Voltage (L-L)	380V	480V**	600V**	4160V
Phase	3	3	3	3
PF	0.8	0.8	0.8	0.8
Hz	60	60	60	60
kW	1750	1750	1750	1750
kVA	2187	2187	2187	2187
Amps	3323	2631	2105	303
skVA@30%				
Voltage Dip	4200	4700	3600	4000
Generator Model*	744RSL4056	743RSL4052	744RSS4292	743FSM4370
Temp Rise	130 °C/40 °C	130 °C/40 °C	130 °C/40 °C	130 °C/40 °C
Connection	4 LEAD WYE	4 LEAD WYE	4 LEAD WYE	6 LEAD WYE

\* Consult the factory for alternate configuration.

\*\* UL 2200 Offered

### CERTIFICATIONS AND STANDARDS

// **Emissions** – EPA Tier 2 Certified

// **Generator set is designed and manufactured in facilities certified to standards ISO 9001:2008 and ISO 14001:2004**

// **Seismic Certification – Optional**

- IBC Certification
- OSHPD Pre-Approval

// **UL 2200 / CSA – Optional**

- UL 2200 Listed
- CSA Certified

// **Performance Assurance Certification (PAC)**

- Generator Set Tested to ISO 8528-5 for Transient Response
- Verified product design, quality and performance integrity
- All engine systems are prototype and factory tested

// **Power Rating**

- Accepts Rated Load in One Step Per NFPA 110
- Permissible average power output during 24 hours of operation is approved up to 85%.

## STANDARD FEATURES\*

- // MTU Onsite Energy is a single source supplier
  - // Global Product Support
  - // 2 Year Standard Warranty
  - // 12V 4000 Diesel Engine
    - 57.2 Liter Displacement
    - Common Rail Fuel Injection
    - 4-Cycle
  - // Complete Range of Accessories
- // Generator
    - Brushless, Rotating Field Generator
    - 2/3 Pitch Windings
    - PMG (Permanent Magnet Generator) supply to regulator
    - 300% Short Circuit Capability
  - // Digital Control Panel(s)
    - UL Recognized, CSA Certified, NFPA 110
    - Complete System Metering
    - LCD Display
  - // Cooling System
    - Integral Set-Mounted
    - Engine-Driven Fan

## STANDARD EQUIPMENT\*

### // Engine

.....  
Air Cleaners  
.....  
Oil Pump  
.....  
Oil Drain Extension and S/O Valve  
.....  
Full Flow Oil Filter  
.....  
Closed Crankcase Ventilation  
.....  
Jacket Water Pump  
.....  
Inter Cooler Water Pump  
.....  
Thermostats  
.....  
Blower Fan and Fan Drive  
.....  
Radiator - Unit Mounted  
.....  
Electric Starting Motor - 24V  
.....  
Governor - Electronic Isochronous  
.....  
Base - Structural Steel  
.....  
SAE Flywheel and Bell Housing  
.....  
Charging Alternator - 24V  
.....  
Battery Box and Cables  
.....  
Flexible Fuel Connectors  
.....  
Flexible Exhaust Connection  
.....  
EPA Certified Engine  
.....

### // Generator

.....  
NEMA MG1, IEEE and ANSI standards compliance for temperature rise and motor starting  
.....  
Sustained short circuit current of up to 300% of the rated current for up to 10 seconds  
.....  
Self-Ventilated and Drip-Proof  
.....  
Superior Voltage Waveform  
.....  
Digital, Solid State, Volts-per-Hertz Regulator  
.....

.....  
No Load to Full Load Regulation  
.....  
Brushless Alternator with Brushless Pilot Exciter  
.....  
4 Pole, Rotating Field  
.....  
130 °C Max. Standby Temperature Rise  
.....  
1 Bearing, Sealed  
.....  
Flexible Coupling  
.....  
Full Amortisseur Windings  
.....  
125% Rotor Balancing  
.....  
3-Phase Voltage Sensing  
.....  
±0.25% Voltage Regulation  
.....  
100% of Rated Load - One Step  
.....  
5% Max. Total Harmonic Distortion  
.....

### // Digital Control Panel(s)

.....  
Digital Metering  
.....  
Engine Parameters  
.....  
Generator Protection Functions  
.....  
Engine Protection  
.....  
CANBus ECU Communications  
.....  
Windows®-Based Software  
.....  
Multilingual Capability  
.....  
Remote Communications to RDP-110 Remote Annunciator  
.....  
Programmable Input and Output Contacts  
.....  
UL Recognized, CSA Certified, CE Approved  
.....  
Event Recording  
.....  
IP 54 Front Panel Rating with Integrated Gasket  
.....  
NFPA 110 Compatible  
.....

\* Represents standard product only. Consult Factory/MTU Onsite Energy Distributor for additional configurations.

## APPLICATION DATA

### // Engine

Manufacturer	MTU
Model	12V4000G84S
Type	4-Cycle
Arrangement	12-V
Displacement: L (in <sup>3</sup> )	57.2 (3,491)
Bore: cm (in)	17 (6.69)
Stroke: cm (in)	21 (8.27)
Compression Ratio	16.5:1
Rated RPM	1,800
Engine Governor	Electronic Isochronous (ADEC)
Max. Power: kWm (bhp)	1,910 (2,561)
Speed Regulation	±0.25%
Air Cleaner	Dry

### // Liquid Capacity (Lubrication)

Total Oil System: L (gal)	260 (68.7)
Engine Jacket Water Capacity: L (gal)	160 (42.3)
After Cooler Water Capacity: L (gal)	40 (10.6)
System Coolant Capacity: L (gal)	583 (154)

### // Electrical

Electric Volts DC	24
Cold Cranking Amps Under -17.8 °C (0 °F)	2,800

### // Fuel System

Fuel Supply Connection Size	#16 JIC 37° Female 1" NPT Adapter Provided
Fuel Return Connection Size	#16 JIC 37° Female 1" NPT Adapter Provided
Max. Fuel Lift: m (ft)	1 (3)
Recommended Fuel	Diesel #2
Total Fuel Flow: L/hr (gal/hr)	960 (254)

### // Fuel Consumption

At 100% of Power Rating: L/hr (gal/hr)	466 (123)
At 75% of Power Rating: L/hr (gal/hr)	352 (93)
At 50% of Power Rating: L/hr (gal/hr)	246 (65)

### // Cooling - Radiator System

Ambient Capacity of Radiator: °C (°F)	40 (104)
Max. Restriction of Cooling Air: Intake and Discharge Side of Rad.: kPa (in. H <sub>2</sub> O)	0.12 (0.5)
Water Pump Capacity: L/min (gpm)	1,117 (295)
After Cooler Pump Capacity: L/min (gpm)	583 (154)
Heat Rejection to Coolant: kW (BTUM)	700 (39,808)
Heat Rejection to After Cooler: kW (BTUM)	500 (28,435)
Heat Radiated to Ambient: kW (BTUM)	157 (8,955)
Fan Power: kW (hp)	48.7 (65.3)

### // Air Requirements


Aspirating: *m <sup>3</sup> /min (SCFM)	144 (5,085)
Air Flow Required for Rad. Cooled Unit: *m <sup>3</sup> /min (SCFM)	1,574 (55,587)
Remote Cooled Applications; Air Flow Required for Dissipation of Radiated Generator Set Heat for a Max. of 25 °F Rise: *m <sup>3</sup> /min (SCFM)	575 (20,196)

\* Air density = 1.184 kg/m<sup>3</sup> (0.0739 lbm/ft<sup>3</sup>)

### // Exhaust System

Gas Temp. (Stack): °C (°F)	465 (869)
Gas Volume at Stack Temp: m <sup>3</sup> /min (CFM)	366 (12,925)
Ma. Allowable Back Pressure: kPa (in. H <sub>2</sub> O)	8.5 (34.1)

## WEIGHTS AND DIMENSIONS



Drawing above for illustration purposes only, based on standard open power 480 volt generator set. Lengths may vary with other voltages. Do not use for installation design. See website for unit specific template drawings.

### System

Open Power Unit (OPU)

### Dimensions (L x W x H)

6,169 x 2,632 x 3,029 mm (242.9 x 103.6 x 119.3 in)

### Weight (less tank)

14,511 kg (31,992 lb)

Weights and dimensions are based on open power units and are estimates only. Consult the factory for accurate weights and dimensions for your specific generator set.

## SOUND DATA

### Unit Type

Level 0: Open Power Unit dB(A)

### Standby Full Load

93.2

Sound data is provided at 7 m (23 ft). Generator set tested in accordance with ISO 8528-10 and with infinite exhaust.

## EMISSIONS DATA

### NO<sub>x</sub> + NMHC

5.16

### CO

0.67

### PM

0.05

**All units are in g/hp-hr and shown at 100% load (not comparable to EPA weighted cycle values).**

Emission levels of the engine may vary with ambient temperature, barometric pressure, humidity, fuel type and quality, installation parameters, measuring instrumentation, etc. The data was obtained in compliance with US EPA regulations. The weighted cycle value (not shown) from each engine is guaranteed to be within the US EPA Standards.

## RATING DEFINITIONS AND CONDITIONS

// Standby ratings apply to installations served by a reliable utility source. The standby rating is applicable to varying loads for the duration of a power outage. No overload capability for this rating. Ratings are in accordance with ISO 8528-1, ISO 3046-1, BS 5514, and AS 2789. Average load factor: ≤ 85%.

// Deration Factor:

**Altitude:** Consult your local MTU Onsite Energy Power Generation Distributor for altitude derations.

**Temperature:** Consult your local MTU Onsite Energy Power Generation Distributor for temperature derations.

C/F = Consult Factory/MTU Onsite Energy Distributor

N/A = Not Available

**MTU Onsite Energy**

A Rolls-Royce Power Systems Brand

[www.mtuonsiteenergy.com](http://www.mtuonsiteenergy.com)